

Configuration Output Options*



- Platen Cover-Y3**
- Single document scanning



- SP DADF-F1**
- Multiple document scanning
 - 100 sheet duplexing automatic document feeder
 - Scans up to 80 images/min (1 sided, 300dpi) and 120 images/min (2 sided, 300dpi)



- SP DADF-E1**
- Multiple document scanning
 - 200 sheet duplexing automatic document feeder
 - Scans up to 135 images/min (1 sided, 300dpi) and 270 images/min (2 sided, 300dpi)



- Booklet Finisher-AH1**
- 2-tray, up to 3,250-sheet capacity
 - Corner and double staple up to 50 sheets (80 gsm)
 - Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
 - Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
 - Supports optional external 2/3 and 2/F4 hole punchers (2/3h Puncher Unit-A1 and 2/F4H Puncher Unit-A1)



- Inner 2 Way Tray-M1**
- Separates copies, prints and faxes
 - Adds a second internal output tray



- Inner Finisher-N1**
- 2-tray, 545-sheet capacity
 - Corner and double stapling up to 50 sheets (80 gsm)
 - Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 40 sheets (80 gsm)



- Utility Tray-B1**




- Copy Tray-T2**




- Paper Deck Unit F3**
- Supports up to A4
 - Media weight 52-105 gsm
 - 2,700 sheets



- Staple Finisher-AH1**
- 2-tray, up to 3,250-sheet capacity
 - Corner and double staple up to 50 sheets (80 gsm)
 - Supports Staple on demand
 - Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
 - Supports optional external 2/3 and 2/F4 hole punchers (2/3h Puncher Unit-A1 and 2/F4H Puncher Unit-A1)



- Cassette Feeding Unit-AZ1**
- Supports up to A3
 - Media weight 52-256 gsm
 - 2 x 550 sheets (80 gsm)



- High Capacity Cassette Feeding Unit-G1**
- Supports A4
 - Media weight 52-256 gsm
 - 2,450 sheets

- Metal Pedestal C3100 series**

- Raises the device, no additional media supply

Partner / Dealer Stamp



CANON INDIA PVT. LTD.
7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase 111, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageFORCE, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON INC., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, LiveCycle, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

© 2026 Canon India Pvt. Ltd.
All rights reserved. Printed in India

imageFORCE C3150

Canon
Delighting You Always

SCALABLE PERFORMANCE TO MEET ANY BUSINESS CHALLENGE



imageFORCE C3150 is built for scalability and versatility, making it the ideal solution for businesses that manage a wide range of document types and volumes.

From high-speed scanning to efficient handling of compact documents like business cards, customers can select the right configuration to simplify digitization and keep workflows efficient.

D² Exposure technology ensures that the imageFORCE C3150 delivers high-resolution images of up to 4,800 x 2,400dpi. With a flexible paper capacity ranging from 1,200 to 6,350 sheets, it supports diverse requirements, ensuring efficient and uninterrupted operations.



CONNECTIVITY

Get the option to access cloud platforms like Google Drive and Dropbox directly from the device. Enjoy mobile printing with Canon PRINT, Apple AirPrint and more for ultimate convenience.



SECURITY

Advanced protection for your data, with features like user authentication and audit logs that help you monitor and mitigate potential risks.



RELIABILITY

Engineered for optimal performance, with intelligent maintenance tools and long-lasting parts that reduce downtime and maximise uptime.



SUSTAINABILITY

Built with up to 30% recycled plastic, supported by eco-friendly packaging and lower energy consumption.

Business Can Be Simple

imageFORCE C3150 Specifications

Main Unit

Machine type

A3 Colour Multifunctional

Core functions

Print, Copy, Scan, Send, Store and Optional Fax

Processor

Dual Core Processor

Control Panel

25.654cm (10.1inch) TFTLCD WSVGA Colour Touch panel

Memory

Standard: RAM: 5.0GB

Storage

Standard: (SSD) 256GB
Optional: (SSD) 1TB

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T
Optional: Wireless LAN (IEEE 802.11a/b/g/n/ac/ax)

Others

Standard: USB 2.0 (Host) x 1, USB 3.0 (Host) x 1, USB 2.0 (Device) x 1
Optional: Serial Interface, Copy Control Interface

Paper Supply Capacity (A4, 80gsm)

Standard: 1,200 sheets
100-sheet Multi-purpose tray x 1
550-sheet Paper cassette x 2
Maximum: 6,350 sheets (with High Capacity Cassette Feeding Unit-G1 + Paper Deck Unit-F3)

Paper output capacity (A4, 80gsm)

Standard: 250 sheets
Maximum: 3,450 Sheets (with Staple Finisher-AH1 or Booklet Finisher-AH1 and Copy Tray-T2)

Supported Media Types

Multi-purpose tray:

Thin, Plain, Recycled, Colour, Heavy, Coated*, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Envelope

* 257~300gsm requires Media Adjustment Kit

Upper Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope

Lower Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope

Supported Media Sizes

Multi-purpose tray:

Standard size:
SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R
Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm
Free Size: 100.0 x 148.0 mm to 304.8 x 457.2 mm
Envelopes: COM10 No.10, Monarch, DL, ISO-C5
Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm

Upper Cassette:

Standard size: A4, A5, A5R, A6R, B5
Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm
Envelopes: ISO-C5

Lower Cassette:

Standard size:
A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R
Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm
Envelopes: COM10 No.10, Monarch, DL

Supported media weights

Multi-purpose tray: 52 to 300 gsm (257 gsm to 300 gsm supported with Media Adjustment Kit)
Upper/Lower Cassette: 52 to 256 gsm
Duplex: 52 to 220 gsm

Warm-up Time

Quick Startup Mode: 4 s or less*

* Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.

From Power On: 10 s or less*

* Time from device power-on, until copy ready (not print reservation)

From Sleep Mode: 10 s or less

Dimensions (W x D x H)

With Platen Cover-Y3: 565 x 745 x 788 mm
With Single Pass DADF-E1: 565 x 745 x 897 mm
With Single Pass DADF-F1: 565 x 745 x 862 mm

Installation Space(W x D)

Basic:

978 x 1,141 mm (with Single Pass DADF-E1 + right door & multi-purpose tray opened + paper cassette opened)

978 x 1,141 mm (with Single Pass DADF-F1 + right door & multi-purpose tray opened + paper cassette opened)

Fully Configured:

1,651 x 1,141 mm (with Single Pass DADF-E1 + Staple Finisher-AH1/Booklet Finisher-AH1 + Copy Tray-T2 extended + paper cassette open)

1,651 x 1,141 mm (with Single Pass DADF-F1 + Staple Finisher-AH1/Booklet Finisher-AH1 + Copy Tray-T2 extended + paper cassette open)

Weight*

*including regular toner
With Platen Cover-Y3: Approx. 79 kg
With Single Pass DADF-E1: Approx. 92 kg
With Single Pass DADF-F1: Approx. 85 kg

Scan Specifications

Type

Standard: Colour Platen
Optional: Platen Cover-Y3, Single Pass DADF-E1* or Single Pass DADF-F1* [2-sided to 2-sided (Automatic with DADF)]
* Multi-Sheet Feed Detection is supported.

DADF: Duplexing Automatic Document Feeder

Document Feeder Paper Capacity (80 gsm)

Single Pass DADF-E1: up to 200 Sheets
Single Pass DADF-F1: up to 100 Sheets

Document Feeder acceptable paper weight

Document Feeder media weight:
Single Pass DADF-E1:
1-sided scanning: 38 to 220 gsm (BW, CL)
2-sided scanning: 38 to 220 gsm (BW, CL)
*An acceptable weights of A6R or smaller is 50 to 220gsm.

Single Pass DADF-F1:
1-sided scanning: 38 to 128 gsm (BW, CL)
2-sided scanning: 50 to 128 gsm (BW, CL)

Supported media sizes

Platen scanning size: up to 297.0 x 431.8 mm
Single Pass DADF-E1:
A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R
Custom size: 69.9 x 139.7 mm to 304.8 x 431.8 mm
Single Pass DADF-F1:
A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R
Custom size: 48.0 x 85.0 mm to 304.8 x 431.8 mm

Scan Speed (images/min A4)

Single Pass DADF-E1:
1-sided Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy)
2-sided Scanning: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)

Single Pass DADF-F1:
1-sided Scanning: 80/80 (300 x 300 dpi, send), 60/60 (600 x 600 dpi, copy)
2-sided Scanning: 120/120 (300 x 300 dpi, send), 60/60 (600 x 600 dpi, copy)

Scan Resolution (dpi)

600 x 600

Pull Scan Specifications

Colour Network ScanGear2 for both TWAIN and WIA
Supported OS: Windows® 11/Server 2016/Server 2019/Server 2022/Server 2025

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP*), SMB, FTP, WebDAV, Mail Box
Optional: Super G3 FAX, IP Fax
* Supported OAuth 2.0 authorization flows in Microsoft 365 and Google Workspace.

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Communication protocol

File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV
E-mail/I-Fax: SMTP, POP3

File Format

TIFF (MMR), JPEG, PDF (Compact, Searchable, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 kbps
G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)

Sending/Receiving Size

Sending: A3, A4, A4R, A5*1, A5R*1, A6R*1, B4, B5*2, B5R*1
Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R
*1 Sent as A4
*2 Sent as B4 short

FAX memory

Up to 30,000 pages (2,000 jobs)

Speed dials

Max. 200

Group dials/destinations

Max. 199 dials

Sequential broadcast

Max. 256 addresses

Memory backup

Yes

Print Specifications

Print Speed (BW and CL)

1-sided: Up to 50 pages/min (A4, A5R), Up to 25 pages/min (A3), Up to 45 pages/min (A5, A6R). Up to 30 pages/min (A4R)

Print Resolution (dpi)

4,800 x 2,400

Page description languages

Standard: UFR II
Optional: Adobe PostScript 3, PCL6/PCL5

Direct Print

Supported file types: PDF, EPS, TIFF/JPEG, and XPS

Printing from mobile and cloud

AirPrint, Mopria® Print Service, IPP Everywhere, Canon PRINT, uniFLOW Online, Universal Print and Cloud Connector

OS Standard Printing

Android/Windows® 11/Chrome OS/macOS (11.2.2 or later) /iOS (15.2 or later)/iPadOS

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2

*1 Optional PCL International Font Set-A1 is required.

*2 Optional Barcode Printing Kit-D1 is required.

Copy Specifications

Copy Speed (BW and CL)

1-sided: Up to 50 pages/min (A4, A5R), Up to 25 pages/min (A3), Up to 45 pages/min (A5, A6R). Up to 22 pages/min (A4R)

First-Copy-Out Time (A4, BW/CL)

Approx. 4.2 / 5.5 seconds or less

Copy resolution (dpi)

600 x 600

Multiple Copies

Up to 999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% to 400% (1% Increments)

Store Specifications

Mail Box (Number supported)

100 User Inboxes,
1 Memory RX Inbox,
50 Confidential Fax Inboxes
Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Client PC: Windows® 11
Concurrent Connections (Max.): SMB:64,
WebDAV:3

Advanced Box available disc space

Standard:16 GB
(With option: max. 480 GB)

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C
Humidity: 20 to 80 % RH (Relative Humidity)

Power source

220-240 V, 50/60 Hz, 10 A

Power consumption

Maximum: Approx. 1,800 W
Sleep mode: Approx. 0.5 W*
* 0.5 W is not available in all circumstances due to certain settings.